

Your Machines: Up and Running.

**Speciality lubricants
for plastics technology**

**Extended lubrication intervals
and reduced tool wear –
across all temperature ranges**



Scan now and
find out more!



Greases



Oils



Sprays



Made in
Germany



Photo © FLPLAST

Product	Application
ELKALUB GLS 563	High-temperature grease (-20 to 250 °C) with a higher base oil viscosity, for the lubrication of moving parts (ejector pins, slides, centring devices) with larger fits in injection moulding tools.
ELKALUB GLS 595	High-temperature grease (-40 to 250 °C) with a lower base oil viscosity, for the lubrication of moving parts (ejector pins, slides, centring devices) with tight fits in injection moulding tools.
ELKALUB GLS 966/N2	Grease for tight fits (-40 to 160 °C)
ELKALUB GLS 993 H1	Grease for tight fits (-40 to 150 °C), with H1 registration
ELKALUB LFC 500	PFPE cleaning agent for preparing surfaces for lubrication with PFPE lubricants.
ELKALUB FLC 3010	Semi-synthetic oil spray (-20 to 120 °C) for corrosion protection, with good penetrating properties, for tight and hard-to-reach areas, with NSF H1 registration and Halal certification.
ELKALUB FLC 400	High-temperature spray (-30 to 300 °C), ideal for demanding applications that place the highest demands on lubrication.
ELKALUB FLC 4010	High-temperature spray (-35 to 180 °C), with H1 registration and Halal certification
ELKALUB FLC 4010 P	High-temperature pump spray (-35 to °C), with H1 registration and Halal certification
ELKALUB FLC 700	Silicone spray (-50 to 170 °C), used as a mould release agent
ELKALUB FLC 900 Clean	H1 cleaning spray for removing dirt from the tool
ELKALUB MBF 370	Corrosion protection products for transport or storage of tools, available as a spray or oil